

NSF Ratings

NSF STANDARD 51 COMPLIANCE

The following is the official NSF listing of KYDEX thermoplastic products that meet either a food or splash zone requirement according to Standard 51: Food Equipment Materials.



NSF International

OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 51 - Food Equipment Materials

This is the Official Listing recorded on July 23, 2015.

SEKISUI Polymer Innovations, LLC
6685 Low Street
Bloomsburg, PA 17815
570-387-6997

Facility: Bloomsburg, PA

Trade Designation	Color	Type of food	Maximum Temperature of Use in °F
Arcylic/PVC Sheet for Food Zone			
Kydex 107	Black	Alcohol less than	100°
	Cobalt Blue	or equal to 8%	
	Gray	Aqueous acidic	
	Red	Aqueous non-acidic	
	Ultramarine Blue	Dry solids	
	White	Oils and fats	
Kydex® 107 MB [1] [2]	Black	All food contact	104°
	Cobalt Blue	types	
	Grey		
	Red		
	Ultramarine Blue		
	White		
	Yellow		
Arcylic/PVC Sheet for Splash Zone			
Kydex 100 Sheet	N/A	N/A	100°
Kydex 110	N/A	N/A	100°
Kydex 130	N/A	N/A	100°
Kydex 150 Sheet	N/A	N/A	100°
Kydex 152WG	N/A	N/A	100°
Kydex 510	N/A	N/A	100°
Kydex 6200	N/A	N/A	N/A
Kydex HD	N/A	N/A	100°
Kydex T Sheet	N/A	N/A	100°
Kydex WG	N/A	N/A	100°
Kydex XD	N/A	N/A	100°
Kydex XD03	N/A	N/A	100°
Kydex XDWG	N/A	N/A	100°

[1] This material cannot be used in contact with liquid milk.

[2] Use of this material must be consistent with the EPA approved label - for use in cutting boards, food and condiment storage containers, gaskets, conveyor belts, countertops, ice making equipment, table tops, and trays.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.

1 of 1



789 N. Dixboro Road, Ann Arbor, Michigan 48105-9723 USA
1-800-NSF-MARK / 734-769-8010
www.nsf.org

81670

Customer Collaboration

6685 Low St, Bloomsburg, PA 17815 USA
Phone: 800.325.3133, +1.570.389.5810
Email: info@kydex.com

appLab™

Phone: 800.682.8758
Email: applab@kydex.com

kydex.com

Because we cannot anticipate or control the many different conditions under which this information and our products may be used, we do not guarantee the applicability of the accuracy of this information or the suitability of our products in any given situation. Users should conduct their own tests to determine the suitability of each product for their particular purposes. Data in the physical property table represents typical values and are to serve only as a guide for engineering design. Results are obtained from specimens under ideal laboratory conditions. Right to change physical properties as a result of technical progress is reserved. THE PRODUCTS DISCUSSED ARE SOLD WITHOUT WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, EITHER EXPRESSED OR IMPLIED, EXCEPT AS PROVIDED IN OUR STANDARD TERMS AND CONDITIONS OF SALE. Buyer assumes all responsibility for loss or damage arising from the handling and use of our products, whether done in accordance with directions or not. In no event shall the supplier or the manufacturer be liable for incidental or consequential damages. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Consult local code and regulatory agencies for specific requirements regarding code compliance, transporting, processing, recycling and disposal of our product. Texture, product grade and other conditions may cause variations in appearance.

This information supersedes all previously published data.